

serija FORWARD



UNUTARNJA JEDINICA	KSAFW-12DCE	KSAFW-18DCE	KSAF-24DCE
VANJSKA JEDINICA	KSAFW-12DCE	KSAFW-18DCE	KSAF-24DCE
Napajanje (ph-V-Hz)	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P
Kapacitet hlađenja (kW)	3.4(0.8-3.8)	5.1(1.3-5.3)	6.7 (1.8-7.4)
Priključak el. energije hlađenje (W)	1340(200-1500)	1670(280-1800)	2200(230-2760)
Kapacitet grijanja (kW)	3.5(0.8-4.0)	5.2(1.3-5.3)	7.2 (1.8-8.2)
Priključak el. energije grijanje (W)	950(200-1400)	1400(220-1500)	2200(230-2530)
SEER (W)	6.2	6.7	6.53
Energetska klasa (h)	A++	A++	A++
SCOP(W)	4.00	4.00	4.09
Energetska klasa (g)	A+	A+	A+
Unutarnja jedinica			
Protok zraka unutarnje jedinice (m3/h)	600/530/480/420	850/770/680/600	1300/1150/1010/870
Razina zvučne snage unutarnje jedinice (dB(A))	54	56	63
Dimenzije unutarnje jedinice - ŠxVxD (mm)	750*285*200	900*310*225	1082*330*233
Težina unutarnje jedinice (kg)	7.5	10	14
Vanjska jedinica			
Razina zvučne snage vanjske jedinice (dB(A))	61	62	66
Dimenzije vanjske jedinice - ŠxVxD (mm)	649*244*456	705*280*530	900*700*350
Težina vanjske jedinice (kg)	18.5	23	39
Rashladno sredstvo	R32	R32	R32
Promjer cijevi tekuća/plinska faza (inch(mm))	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
Max duljina cjevovoda (m)	20	20	25
Max visinska razlika (m)	10	10	15
Područje rada hlađenje/grijanje (°C) min~max	15~48/-15~32	15~48/-15~32	16~49/-15~30
Razmak između nosača (cm)	48	48	63

ČIST ZRAK



Filter



Samočišćenje



Auto restart



Samodijagnostika i automatska zaštita

UDOBNOST



Skriveni LED display



Timer



Turbo način rada



IFeel / Slijedi me funkcija



A++
Energetska klasa

WiFi (uključen*)
*24k priprema

R32
Freon

